

OFFICE OF THE SUPERINTENDENT, POWER AND LIGHTING, MYSORE.

Notification dated 5th April 1939.

1. Sealed tenders in triplicate will be received in the office of the Superintendent, Power and Lighting, Mysore, superscribed with the name of the work mentioned below :—
2. The plans connected with the work may be seen at the Office of the undersigned at all working hours. The copy, if required, will be made available on payment of Re. 1 per set.
3. The tenders should be drawn up strictly in conformity with the specifications furnished, writing out the rates at which each item of work will be executed in figures as well as in words, failing which no cognisance will be taken of the tender. No items other than those noted in the statement should be included as the items cover provision for all sundries, repairs to damaged masonry and painting.
4. The materials to be used on the work should be of best quality conforming to the specification of this Department and B.S. or A.I.E.E. specification. Mention should also be made of the manufacture and the catalogue numbers of materials offered. Teakwood planks to be used on the work should be free from knots, cracks and well seasoned. No planks less than 12" in width will be permitted to be used unless it is to make up the difference in size of the board required. Only the lap joints should be adopted in all cases. Lamp holders, ceiling roses, etc., should be of reinforced bakelite material.
5. The undersigned reserves the right to reject the tenders without assigning any reason therefor.
6. The successful tenderer will be required to deposit an earnest money of Rs. 45 (Rupees forty-five only) and execute an agreement within two days from the date of intimation of acceptance of tender. He should send samples of all the materials required for the work mounted on a board and start the work after obtaining the approval of the undersigned and with regard to the same and carry out the wiring following the rules of this Department as well as that of the Institution of Electrical Engineers. He should also be prepared to adopt any change in the location of control units and other outlets that might be suggested by the undersigned during the progress of the work without extra cost, if the tender is not materially affected by such deviations. It should also be noted that the control switches, etc., should be grouped and installed in inconspicuous corners.
7. The undersigned reserves the right also to reject the work either in full or in part if he finds the work not carried out in terms of the specifications or is otherwise dissatisfied with the workmanship.
8. *Name of work* :—Installing electric lights, etc., to the Northern Extension of the Central Police Station. (Both floors).
9. Last date and time of receiving the tender. 25th April 1939 at 3 P.M.
10. Date and time of opening the tender in public—25th April 1939 at 4 P.M.
11. A period of 3 weeks will be allowed for the completion of the work in all respects, from the date of final acceptance of the tender. A penalty of Rs. 10 (ten) for each day of delay over the stipulated period for completion of the work during the 1st week and Rs. 20 (twenty) in the 2nd week will be enforced. If there be further delay, the department will take charge of the installation at whatever stage it might be and arrange for the completion entirely at the risk of the tenderer.
12. The firm executing the work should arrange while handing over the installation to this Department to pass a certificate of guarantee for the continuance of satisfactory service to the installation for a period of 12 calendar months from the date of handing over charge to this Department, while uninterrupted power supply is maintained. Further, it will be obligatory on the part of the firm to attend to any defects in the installation that might arise due to bad work during the above period without any return for service rendered.
13. *Details of work* :—The quantities given below are not guaranteed and are subject to variation at the time of executing the work.

INSTALLING ELECTRIC LIGHTS TO THE SHOPS ADJOINING THE 'HAMILTON BUILDING,' DODDAPET, MYSORE.

*Particulars.**Quantity.*

PART I—MAINS.

- | | | |
|---|----------|----|
| (1) Supplying and laying 7/044 SWG. twin conductor, paper insulated, lead covered double steel tape armoured cable in a trench 3 ft. deep surrounding the same with 3 inch of fine sand and enclosing the ends in pole and indoor type cast iron junction boxes, filled with insulating compound, the vertical run of the cable at the pole end in 20 ft. of 1½" galvd. pipe with a bend supported with clamps using No. 7/.044 SWG. insulated wire and accessories | .. Ft. | 60 |
| (2) Supplying and running mains in ¾" heavy gauge welded conduit with large round T-junction boxes, berds and 7/.044 SWG. insulated wire and accessories | .. " | 70 |
| (3) Do sub-mains in ¾" heavy gauge welded conduit from the mains to the distribution board using No. 7/036 SWG. insulated wire and accessories | .. " | 40 |
| (4) Supplying, fixing and wiring T.W. board 15"×12"×1" with 2" battens and ½" rear board equipping it with 2 S.P. iron clad cut outs with fuses 15 amp. one 10 amp. D.P.S.T. iron clad switch with fuses using No. 7/.029 SWG insulated wire and accessories | .. No. | 5 |
| (5) Earthing cable armouring conduit, ironclad switches and cut outs, etc. | .. Item. | |

*Particulars.**Quantity.*

PART II.—INTERIOR WIRING.

- | | | |
|---|-----|---|
| (1) Supplying, fixing and wiring in T.W. 2 way casing treated with 2 coats of shellac varnish for drop-lights complete with 2 plate bakelite ceiling rose, flexible cord, B.C.C.G. reinforced bakelite lampholder, 5 amp. S.P. control switch with reinforced bakelite cover, using No. 7/.029 and 3/.036 SWG. insulated wire for mains and taps respectively and accessories | No. | 5 |
| (2) Do for cubalite blocks 6" complete with stout (similar to the one attached to the Central building) ceiling plate B.C. lamp holder, etc., Crompton Engineering Co's Cat. No. H. 23 using 5 amp. S.P. control switch and accessories as per specification | No. | 3 |
| (3) Do combined wall plug and switch 5 amp. with nipple as per specification | " | 5 |
| (4) Supplying and fixing shades green and white enamelled 10"×5" | " | 5 |

Abstract.

Part I	..	..	..	..	..
Part II	..	..	..	..	..

INSTALLING ELECTRIC LIGHTS TO THE POLICE SUB-INSPECTOR'S QUARTERS IN THE 1ST FLOOR
OF THE BUILDING ADJOINING THE "HAMILTON BUILDING," DODDAPET, MYSORE.

*Particulars.**Quantity.*

PART I—MAINS.

- | | | |
|---|-------|----|
| (1) Supplying and laying No. 7/.036 SWG twin conductor paper insulated lead covered double steel tape armoured juteserved for 1,000 volts pressure underground cable in a trench 3 ft. deep surrounding it with 3" of fine sand enclosing the ends of the cable in pole and indoor type cast iron junction boxes filled with insulating compound and the exposed portion of the cable at the pole end in 20 ft. of galvanised pipe 1½" dia. with a bend supported with clamps, etc., using No. 7/.036 SWG. insulated wire and accessories | Ft. | 60 |
| (2) Supplying and running mains in ¾" heavy gauge welded conduit with bends, etc., using No. 7/.036 SWG. insulated wire and accessories | " | 80 |
| (3) Supplying, fixing and wiring T.W. board 15"×12"×1" with battens and rear board equipping it with a D.P. 10 amp. iron clad switch with fuses using No. 7/.029 SWG. insulated wire and accessories | No. | 1 |
| (4) Earthing | Item. | |

PART II—INTERIOR WIRING.

- | | | |
|--|-----|---|
| (1) Supplying, fixing and wiring in 2"×1" teak wood casing treated with 2 coats of shellac varnish for drop lights complete with 2 plate bakelite ceiling rose flexible cord B.C.C.G. reinforced bakelite lamp holder 5 amp. S.P. control switch with reinforced bakelite cover using No. 7/.029 and 3/.036 SWG. insulated wires for mains and taps respectively and accessories | No. | 8 |
| (2) Supplying, fixing and wiring for ⅝" brazied conduit pendants 3 to 4 ft. long complete with stout ceiling plate B.C. lamp holder, 5 amp. S.P. control switch, etc., as per specification above | " | 2 |
| (3) Supplying, fixing and wiring for cubalite block 6" complete with stout (similar to one attached to the Central Building) ceiling plate B.C. lamp holder, etc., Crompton Engineering, Co's. Cat. No. H. 23 using 5 amp. S.P. control switch etc., as per specification above | " | 3 |
| (4) Do for combined wall plug and switch with nipple 5 amp. as per specification | " | 1 |
| (5) Do for drop light complete with ceiling rose B.C. lamp holder flexible cord, using 2 two way control switches and accessories as per specification | " | 1 |
| (6) Supplying, fixing and wiring for water tight fitting complete with gooseneck cast iron enamelled reflector B.C. lamp holder well glass, etc., using 5 amp. S.P. control switch and accessories | " | 1 |
| (7) Supplying, and fixing shades tin enamelled 10"×5" | " | 7 |
| (8) Do green and white opal 10"×5" | " | 4 |

Abstract.

Part I	..	..	..	..	..
Part II	..	..	..	..	..

Notification dated 5th April 1939.

1. Sealed tenders in triplicate will be received in the office of the Superintendent, Power and Lighting, Mysore, superscribed with the name of the work mentioned below.
2. The plans connected with the work may be seen at the office of the undersigned at all working hours. The copy, if required, will be made available on payment of Re. 1 per set.
3. The tenders should be drawn up strictly in conformity with the specifications furnished, writing out the rates at which each item of work will be executed in figures as well as in words, failing which no cognisance will be taken of the tender. No items other than those noted in the statement should be included as the items cover provision for all sundries, repairs to damaged masonry and painting.
4. The materials to be used on the work should be of best quality conforming to the specification of this Department and B.S. or A.I.E.E. specification. Mention should also be made of the manufacture and the catalogue numbers of materials offered. Teakwood planks to be used on the work should be free from knots, cracks and well seasoned. No planks less than 12" in width will be permitted to be used unless it is to make up the difference in size of the board required. Only the lap joints should be adopted in all cases. Lamp holders, ceiling roses, etc., should be of reinforced bakelite material.
5. The undersigned reserves the right to reject the tenders without assigning any reason therefor.
6. The successful tenderer will be required to deposit an earnest money of Rs. 45 (Rupees forty-five only) and execute an agreement within two days from the date of intimation of acceptance of tender. He should send samples of all the materials required for the work mounted on a board and start the work after obtaining the approval of the undersigned and with regard to the same and carry out the wiring following the rules of this Department as well as that of the Institution of Electrical Engineers. He should also be prepared to adopt any change in the location of control units and other outlets that might be suggested by the undersigned during the progress of the work without extra cost, if the tender is not materially affected by such deviations. It should also be noted that the control switches, etc., should be grouped and installed in inconspicuous corners.
7. The undersigned reserves the right also to reject the work either in full or in part if he finds the work not carried out in terms of the specifications or is otherwise dissatisfied with the workmanship.
8. *Name of the work.*—Installing electric lights to the Railway Station at Yeliyur (Mandya Taluk), Mysore State Railway.
9. Last date and time of receiving the tender—22nd April 1939 at 3 P.M.
10. Date and time of opening the tender in public—22nd April 1939 at 4 P.M.
11. A period of 3 weeks will be allowed for the completion of the work in all respects, from the date of final acceptance of the tender. A penalty of Rs. 10 (ten) for each day of delay over the stipulated period for completion of the work during the 1st week and Rs. 20 (twenty) in the 2nd week will be enforced. If there be further delay, the department will take charge of the installation at whatever stage it might be and arrange for the completion entirely at the risk of the tenderer.
12. The firm executing the work should arrange, while handing over the installation to this Department, to pass a certificate of guarantee for the continuance of satisfactory service to the installation for a period of 12 calendar months from the date of handing over charge to this Department, while uninterrupted power supply is maintained. Further, it will be obligatory on the part of the firm to attend to any defects in the installation that might arise due to bad work during the above period without any return for service rendered.
13. *Details of work.*—The quantities given below are not guaranteed and are subject to variation at the time of executing the work.

INSTALLING ELECTRIC LIGHTS TO THE RAILWAY STATION AT YELIUR (MANDYA TALUK),
MYSORE STATE RAILWAY.

Particulars.

Quantity.

PART I—STATION BUILDING.

- | | |
|---|-----------|
| (1) Supplying and laying No. 10 B. & S. twin conductor paper insulated lead covered, double steel armoured jute served underground cable, insulated for 1,000 volts pressure in a trench 3 ft. deep surrounding the cable with 3" of fine sand and enclosing the ends of the cable in indoor and outdoor type C.I. junction boxes filled with bitumen and also enclosing the cable on the tapping pole and below the railway line in 1½" galvanised pipe, using necessary accessories | R.ft. 250 |
| (2) Supplying, fixing and wiring a varnished teakwood board 21"×15"×1" with batten and rear board equipping the same with a 15 amp. D.P.S.T. ironclad switch with fuses, one two-way distribution box ironclad D.P.H.O. pattern 'Neata' 10 amp. per way with 10 amp. circuit switches using necessary accessories | No. 1 |
| (3) Do in teakwood casing 2"×1" for drop lights complete with ceiling rose, flexible cord, B.C. lamp holder, 5 amp. tumbler switch, using No. 14 B. & S. insulated wire and accessories | " 2 |
| (4) Do for ⅝" braised conduit pendant 1 to 2 ft. long complete with C.I. ceiling plate, B.C. lamp holder, etc., as per specification above | " 3 |
| (5) Do for bracket brass 9"×½" as per specification above | " 1 |
| (6) Do for water-tight fitting complete with gooseneck, well glass, B.C. lamp holder, etc., as per above specification | " 1 |

Particulars.	Quantity.
(7) Supplying and fixing enamel shades	No. 3
(8) Do white opal	3
(9) Lamps 40 to 60 watts. B.C. 230 volts	7
(10) Grounding	Item

PART II—INSTALLING PLATFORM LIGHTS.

- (1) Supplying and laying twin conductor No. 12 B. & S. paper insulated, lead covered, double steel tape armoured, jute served, underground cable, in a trench 3 ft. deep surrounding the same with 3 inches of fine sand and enclosing the ends of the cable in indoor type C.I. junction boxes filled with bitumen and connecting up the same with feeder circuit, using necessary accessories .. R.ft. 500
- (2) Supplying and fixing and wiring 4" tubular pole 14 ft. long with cement concrete base as per bottom of fluted C.I. ornamental lamp post with an opening to fix up switch with fuse, equipping it with a special bracket (as per sketch) provided with a terrace fitting GEC Cat. No. 25335, complete with B.C. lamp holder, using underground C.I. boxes 2 and 3-way No. 12 B. & S. twin lead covered cable 5 amp. bakelite switch, one 5 amp. bow cut out housed at the cement concrete case .. No. 4
- (3) Supplying and fixing lamps 230 volts, 200 watts. B.C. .. 4

M. M. ALI KHAN,
Superintendent.

OFFICE OF THE SUPERINTENDENT, POWER AND LIGHTING, BHADRAVATI.

Abstract Notification.

The attention of the public is invited to the detailed Tender Notification, dated 30th March 1939 calling for tenders for "Running a three-phase Power Line to the Work-shop at Shimoga Town Railway Station," published in Part VI, pages 611-612 of the *Mysore Gazette*, dated 30th March 1939. The latest date for receiving tenders is 24th April 1939.

K. SUBBA RAO,
Superintendent.

PRIVATE ADVERTISEMENTS.

IN THE COURT OF THE PRINCIPAL SUB-JUDGE AT BANGALORE.

Insolvency Application No. 44 of 1938-39.

- B. S. Krishna Iyengar, son of B. Srinivasa Iyengar, aged about 50 years, Electric Operator, (C) Station, Bangalore City *Petitioner.*
- vs.*
- (1) Rupraj, (2) N. P. Lakshmiah, (3) A. Shukur Brothers, (4) Abdul Gaffoor, (5) Dalir Khan, (6) Jariff Khan, (7) Pillappa, (8) Kundan Mull, (9) Valli Mahaud Khan, (10) Nagesa Rao, (11) Zarib Khan *Opponents.*

Whereas the petitioner B. S. Krishna Iyengar, has applied to this Court, by a petition dated the 20th day of February 1939, to be declared an insolvent under the Mysore Insolvency Act VI of 1911, and your name appears in the list of creditors filed by the aforesaid debtor, this is to give you notice that the Court has fixed the 23rd day of June 1939, for the hearing of the aforesaid petition and the examination of the debtor. If you desire to be represented in the matter, you should attend in person or by duly instructed pleader.

Insolvency Application No. 56 of 1938-39.

- A. R. Ramaswamiah, son of A. Ramachandra Rao, No. 43, III Road, Chamarajpet, Bangalore City *Petitioner.*
- vs.*
- (1) M. G. Siddaramanna, (2) S. Appanna, (3) N. P. Lakshmiah, (4) B. S. Venkatesa Pandit, (5) Nidha Khan, (6) G. Narasinga Rao *Opponents.*

Whereas the petitioner A. R. Ramaswamiah, has applied to this Court, by a petition dated the 28th day of March 1939, to be declared an insolvent under the Mysore Insolvency Act VI of 1911, and your name appears in the list of creditors filed by the aforesaid debtor, this is to give you notice that the Court has fixed the 26th day of May 1939, for the hearing of the aforesaid petition and the examination of the debtor. If you desire to be represented in the matter, you should attend in person or by duly instructed pleader.

U. D. NARAYANA MURTHY,
Principle Sub-Judge.